

KFP's Most Advanced Structural Firefighting Attack Line

COLORS:



General Applications:

- Designed for low pressure/high volume nozzles
- Available as 1 3/4" attack line and 2 1/2" master flow line

Construction:

Composed of an outer jacket woven from 100% high tenacity synthetic yarn and an inner liner consisting of a one-piece extruded through-the-weave nylon reinforced NBR rubber tube.

Service Temperature Range:

Burn-Through Resistance – Boasts outstanding burn through resistance, being capable of withstanding a surface temperature in excess of +1100°F (+593°C) for a minimum of one minute*, at a static pressure of 100 psi, without damage or rupture to the synthetic reinforcement.
*As per BS 6391, heat resistance test.

Cold Resistance – Cold resistant to -40°F (-40°C).



Features and Advantages:

- Outstanding kink resistance.
- Resists burn-through for a full minute*.
- Perfect fit of outer jacket and inner tube.
- High tenacity polyester/polyamide outer jacket.
- Oversized inner jacket for increased water flow.
- Lower friction loss than other double jacket hoses.
- Exceptional heat and cut resistance.
- Burst Resistance – Will not burst catastrophically even with a puncture through both the outer jacket and liner.
- Meets or exceeds National Fire Protection Association (NFPA) 1961 Standard on Fire Hose (current edition).
- ISO 9001 - ARMTEX® HP™ fire hose products are manufactured in a registered facility in Barcelona, Spain.
- 10-year warranty.

Packaging:

Available in 25', 50' and 100' lengths.

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS OR DISCONTINUE PRODUCTS WITHOUT PRIOR NOTICE.

KFP's Most Advanced Structural
Firefighting Attack Line

Nominal Specifications

Part Number*	Size (in)	Color	Coupling Size (in)	Coupling Type	Bowl Size (in)	Service Test (psi)	Proof Test (psi)	Burst Test (psi)	Available Lengths (ft)	Weight Uncoupled (lbs/ft)
HP175RXXX-NH150	1 3/4	Red	1 1/2	NST	2 1/8	580	1160	1740	25/50/100	0.40
HP175RXXX-NH150-L	1 3/4	Red	1 1/2	NST Liberator	2 1/8	580	1160	1740	25/50/100	0.40
HP175RXXX-NP150	1 3/4	Red	1 1/2	NPSH	2 1/8	580	1160	1740	25/50/100	0.40
HP175RXXX-NP150-L	1 3/4	Red	1 1/2	NPSH Liberator	2 1/8	580	1160	1740	25/50/100	0.40
HP175BXXX-NH150	1 3/4	Blue	1 1/2	NST	2 1/8	580	1160	1740	25/50/100	0.40
HP175BXXX-NH150-L	1 3/4	Blue	1 1/2	NST Liberator	2 1/8	580	1160	1740	25/50/100	0.40
HP175BXXX-NP150	1 3/4	Blue	1 1/2	NPSH	2 1/8	580	1160	1740	25/50/100	0.40
HP175BXXX-NP150-L	1 3/4	Blue	1 1/2	NPSH Liberator	2 1/8	580	1160	1740	25/50/100	0.40
HP175GXXX-NH150	1 3/4	Green	1 1/2	NST	2 1/8	580	1160	1740	25/50/100	0.40
HP175GXXX-NH150-L	1 3/4	Green	1 1/2	NST Liberator	2 1/8	580	1160	1740	25/50/100	0.40
HP175GXXX-NP150	1 3/4	Green	1 1/2	NPSH	2 1/8	580	1160	1740	25/50/100	0.40
HP175GXXX-NP150-L	1 3/4	Green	1 1/2	NPSH Liberator	2 1/8	580	1160	1740	25/50/100	0.40
HP175YXXX-NH150	1 3/4	Yellow	1 1/2	NST	2 1/8	580	1160	1740	25/50/100	0.40
HP175YXXX-NH150-L	1 3/4	Yellow	1 1/2	NST Liberator	2 1/8	580	1160	1740	25/50/100	0.40
HP175YXXX-NP150	1 3/4	Yellow	1 1/2	NPSH	2 1/8	580	1160	1740	25/50/100	0.40
HP175YXXX-NP150-L	1 3/4	Yellow	1 1/2	NPSH Liberator	2 1/8	580	1160	1740	25/50/100	0.40
HP175OXXX-NH150	1 3/4	Orange	1 1/2	NST	2 1/8	580	1160	1740	25/50/100	0.40
HP175OXXX-NH150-L	1 3/4	Orange	1 1/2	NST Liberator	2 1/8	580	1160	1740	25/50/100	0.40
HP175OXXX-NP150	1 3/4	Orange	1 1/2	NPSH	2 1/8	580	1160	1740	25/50/100	0.40
HP175OXXX-NP150-L	1 3/4	Orange	1 1/2	NPSH Liberator	2 1/8	580	1160	1740	25/50/100	0.40
HP250BXXX-NH250	2 1/2	Blue	2 1/2	NST	3	400	800	1200	25/50/100	0.60
HP250BXXX-NH250-L	2 1/2	Blue	2 1/2	NST Liberator	3	400	800	1200	25/50/100	0.60
HP250YXXX-NH250	2 1/2	Yellow	2 1/2	NST	3	400	800	1200	25/50/100	0.60
HP250YXXX-NH250-L	2 1/2	Yellow	2 1/2	NST Liberator	3	400	800	1200	25/50/100	0.60
HP250OXXX-NH250	2 1/2	Orange	2 1/2	NST	3	400	800	1200	25/50/100	0.60
HP250OXXX-NH250-L	2 1/2	Orange	2 1/2	NST Liberator	3	400	800	1200	25/50/100	0.60

*XXX = Available Lengths

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS OR DISCONTINUE PRODUCTS WITHOUT PRIOR NOTICE.