

T313AA EVOLUTION



Liquid cooling - hard wall - EPDM

UL 94 V0

Tube: black peroxide cured EPDM, calcium and zinc free.

Reinforcement: high tensile textile cords with embedded steel helix wire.

Cover: black EPDM - abrasion, ozone and flame resistant.

Application: cooling liquids in applications where tight bend radius is required.

Temperature: -40 °F +248 °F (-40 °C +120 °C)

ID		OD		Max. Working Pressure (psi)	Burst Pressure (psi)	Vacuum %	Bend Radius		Weight (lbs/ft)
(in)	(mm)	(in)	(mm)				(in)	(mm)	
1	25.0	1.42	36.0	150	600	100	1.42	36.0	0.52
1 1/4	32.0	1.73	44.0	150	600	100	1.89	48.0	0.68
1 1/2	38.0	1.97	50.0	150	600	100	2.24	57.0	0.79
2	51.0	2.52	64.0	150	600	100	2.99	76.0	1.18
2 1/2	63.0	3.03	77.0	150	600	90	4.96	126.0	1.57
3	76.0	3.58	91.0	150	600	90	5.98	152.0	1.96
4	102.0	4.57	116.0	150	450	90	12.04	306.0	2.51
6	152.0	6.73	171.0	150	375	80	23.93	608.0	4.75

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.