







EDITION 0321



KURIYAMA Hydraulic

What makes our stainless steel fittings better? Kuriyama Hydraulic Connections stainless steel fittings share crimp dimensions with our trusted Top Coat plated carbon steel fittings! Matching crimp dimensions for both lines takes the guess work and liability out of the distributor and end users hands. Both our Top Coat fittings and our new stainless steel fittings are manufactured by Alfagomma, SPA — the world class leader in hydraulic hose, fittings and quick release couplings. A proven validated crimp system from two world class leaders, Kuriyama and Alfagomma[®].

Stainless steel fittings are now available for use on Kuriyama Hydraulic hoses


Some of these hoses include: TR1MT/HT, TR2MT/HT, TF2MT/ST, AT3KMT/ST, TR14TB, TR14C, TR5/ HT, E4K and TR4XF hoses.

Stainless steel fittings are available in the following popular configurations and sizes:

- MNPT Male Pipe 1/4" 2" MNPS Male Pipe Swivel 1/4" 1" FJDH Female JIC 1/4" 2"
- FJ45 Female JIC 45° 1/4" 1" FJ9M Female JIC 90° Medium Drop 1/4" 1"
- BSPT/JIS Male Tapered 1/2" 1" BSPP Male Parallel 1/2" 1"

For more information, please contact us at sales@kuriyama.com

ALFAGOMMA[®] Two-Piece Fittings – A Series Non-Skive Ferrules




KURIYAMA Hydraulic

AF1 – STAINLESS STEEL


Part Number	Dash	Hose ID Size		B OD	L Length	Weight
i art Number	Size	(in)	(mm)	(mm)	(mm)	(lbs/each)
AF1-04-SS	04	1/4	6.4	22	24.7	0.06
AF1-06-SS	06	3/8	9.5	26	29.7	0.10
AF1-08-SS	08	1/2	12.7	29	30.5	0.11
AF1-10-SS	10	5/8	15.9	32	30.5	0.12
AF1-12-SS	12	3/4	19.0	36	36.0	0.17

AF2 – STAINLESS STEEL



Part Number	Dash	Hose ID Size		B OD	L Length	Weight
i ait nuindei	Size	(in)	(mm)	(mm)	(mm)	(lbs/each)
AF2-04-SS	04	1/4	6.4	23	24.7	0.07
AF2-06-SS	06	3/8	9.5	27	29.7	0.10
AF2-08-SS	08	1/2	12.7	30	30.5	0.12
AF2-10-SS	10	5/8	15.9	33	30.5	0.13
AF2-12-SS	12	3/4	19.0	37	36.0	0.18
AF2-16-SS	16	1	25.4	45	36.7	0.24

AF4 – STAINLESS STEEL



Part Number	Dash	Hose	ID Size	B OD	L Length	Weight (Ibs/each)
	Size	(in)	(mm)	(mm)	(mm)	
AF4-06-SS	06	3/8	9.5	30	28.0	0.11
AF4-08-SS	08	1/2	12.7	34	33.9	0.16
AF4-10-SS	10	5/8	15.9	38	36.6	0.20
AF4-12-SS	12	3/4	19.0	42	39.5	0.28
AF4-16-SS	16	1	25.4	50	45.4	0.51

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.




ALFAGOMMA[®] Two-Piece Fittings – A Series Non-Skive Ferrules

ł	L
B	
ļ	()transatranatrans

Part Number Size OD (in) Construction (mm) OD (mm) Length (mm) Horght (lbs/each) AFX-04-SS 04 1/4 6.4 23 24.7 0.07 AFX-05-SS 05 5/16 7.9 25 24.7 0.08 AFX-06-SS 06 3/8 9.5 27 29.7 0.10 AFX-08-SS 08 1/2 12.7 30 30.5 0.11 AFX-10-SS 10 5/8 15.9 34 35.5 0.15 AFX-12-SS 12 3/4 19.0 38 36.0 0.17
AFX-05-SS055/167.92524.70.08AFX-06-SS063/89.52729.70.10AFX-08-SS081/212.73030.50.11AFX-10-SS105/815.93435.50.15
AFX-06-SS 06 3/8 9.5 27 29.7 0.10 AFX-08-SS 08 1/2 12.7 30 30.5 0.11 AFX-10-SS 10 5/8 15.9 34 35.5 0.15
AFX-08-SS 08 1/2 12.7 30 30.5 0.11 AFX-10-SS 10 5/8 15.9 34 35.5 0.15
AFX-10-SS 10 5/8 15.9 34 35.5 0.15
AFX-12-SS 12 3/4 19.0 38 36.0 0.17
AFX-16-SS 16 1 25.4 48 42.5 0.28
AFX-20-SS 20 1 1/4 31.8 53 56.5 0.42
AFX-24-SS 24 1 1/2 38.1 60 61.5 0.45
AFX-32-SS 32 2 50.8 76 73.5 0.82

AFX – STAINLESS STEEL

AFT – STAINLESS STEEL



Part Number	Dash	Hose ID Size		B OD	L Length	Weight
i ai t Nullibei	Size	(in)	(mm)	(mm)	(mm)	(lbs/each)
AFT-03	03	3/16	4.8	14.0	20	0.02
AFT-04	04	1/4	6.4	15.0	25	0.03
AFT-05	05	5/16	7.9	17.2	25	0.04
AFT-06	06	3/8	9.5	22.0	25	0.07
AFT-08	08	1/2	12.7	25.0	30	0.08
AFT-10	10	5/8	15.9	30.0	33	0.11
AFT-12	12	3/4	19.0	35.0	37	0.15
AFT-16	16	1	25.4	42.0	45	0.26
AFT-20	20	1 1/4	31.8	50.0	48	0.34
AFT-24	24	1 1/2	38.1	57.0	58	0.48
AFT-32	32	2	50.8	73.0	67	0.73


Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.



ALFAGOMMN Two-Piece Fittings – A Series

Inserts – US End Configurations

MNPT MALE 60° SEAT STAINLESS STEEL



Part Number	Dash	Hose ID Size		F	F Thread		Hex Dia.	Weight
	Size	(in)	(mm)	Dash Size	Size (in) - TPI	Factor (mm)	CH1 (mm)	(lbs/each)
A-0404-MNPT-SS	04	1/4	6.4	04	1/4-18	26.8	17	0.06
A-0606-MNPT-SS	06	3/8	9.5	06	3/8-18	27.8	19	0.09
A-0808-MNPT-SS	08	1/2	12.7	08	1/2-14	32.1	22	0.17
A-1008-MNPT-SS	10	5/8	15.9	08	1/2-14	32.1	27	0.23
A-1012-MNPT-SS	10	5/8	15.9	12	3/4-14	34.1	27	0.24
A-1212-MNPT-SS	12	3/4	19.0	12	3/4-14	34.6	27	0.26
A-1616-MNPT-SS	16	1	25.4	16	1-11 1/2	44.4	36	0.53
A-2020-MNPT-SS	20	1 1/4	31.8	20	1 1/4-11 1/2	49.0	46	0.90
A-2424-MNPT-SS	24	1 1/2	38.1	24	1 1/2-11 1/2	50.5	50	1.10
A-3232-MNPT-SS	32	2	50.8	32	2-11 1/2	54.2	65	2.87

F C C

MNPS MALE SWIVEL 60° SEAT STAINLESS STEEL

	Dash	Hose ID Size		F Thread		C Cut-Off	Hex Dia.	Weight
Part Number	Part Number Size	(in)	(mm)	Dash Size	Size (in) - TPI	Factor (mm)	CH1 (mm)	(lbs/each)
A-0404-MNPS-SS	04	1/4	6.4	04	1/4-18	37.6	17	0.09
A-0606-MNPS-SS	06	3/8	9.5	06	3/8-18	37.5	22	0.15
A-0808-MNPS-SS	08	1/2	12.7	08	1/2-14	42.3	25	0.25
A-1008-MNPS-SS	10	5/8	15.9	08	1/2-14	45.1	27	.027
A-1012-MNPS-SS	10	5/8	15.9	12	3/4-14	47.3	27	0.29
A-1212-MNPS-SS	12	3/4	19.0	12	3/4-14	50.1	32	0.31
A-1616-MNPS-SS	16	1	25.4	16	1-11 1/2	57.9	41	0.63

BSPT/JIS MALE TAPERED

	Part Nur
ALL DADAMAN	A-0808
+	A-1010
CH1	A-1212

-	Dash	Hose ID Size		F Thread		C Cut-Off	Hex Dia.	Weight
Part Number	Size (in)		(mm)	Dash Size	Size (in) - TPI	Factor (mm)	CH1 (mm)	(lbs/each)
A-0808-MBPT-SS	08	1/2	12.7	08	1/2-14	34.1	22	0.17
A-1010-MBPT-SS	10	5/8	15.9	10	5/8-14	34.1	30	0.22
A-1212-MBPT-SS	12	3/4	19.0	12	3/4-14	34.6	27	0.27
A-1616-MBPT-SS	16	1	25.4	16	1-11	43.4	36	0.53

BSP MALE PARALLEL 60° SEAT


-	— C — ►	
Ŧ		
F		
<u>.</u>	a a a a a a a a a a a a a a a a a a a	
	CH1	

	Dash Size	Hose	ID Size	FΤ	hread	C Cut-Off	Hex Dia.	Weight
Part Number		(in)	(mm)	Dash Size	Size (in) - TPI	Factor (mm)	CH1 (mm)	(lbs/each)
A-0808-MBPP-SS	08	1/2	12.7	08	1/2-14	32.1	27	0.20
A-1010-MBPP-SS	10	5/8	15.9	10	5/8-14	36.1	30	0.27
A-1212-MBPP-SS	12	3/4	19.0	12	3/4-14	34.6	32	0.31
A-1616-MBPP-SS	16	1	25.4	16	1-11	40.4	41	0.58

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.



ALFAGOMMA Two-Piece Fittings – A Series



CH2

fi fi

CH2

Part Number	Dash Size	Hose ID Size		F Thread		C Cut-Off	Hex Dia.	Hex Dia.	Weight
		(in)	(mm)	Dash Size	Size (in) - TPI	Factor (mm)	CH1 (mm)	CH2 (mm)	(lbs/each)
A-0404-FJDH-SS	04	1/4	6.4	04	7/16-20	19.6	14	16	0.06
A-0606-FJDH-SS	06	3/8	9.5	06	9/16-18	21.3	17	19	0.10
A-0808-FJDH-SS	08	1/2	12.7	08	3/4-16	25.6	19	25	0.2
A-1010-FJDH-SS	10	5/8	15.9	10	7/8-14	27.6	24	27	0.27
A-1212-FJDH-SS	12	3/4	19.0	12	1 1/16-12	28.6	27	32	0.35
A-1616-FJDH-SS	16	1	25.4	16	1 5/16-12	32.9	32	38	0.62
A-2020-FJDH-SS	20	1 1/4	31.8	20	1 5/8-12	39.1	41	50	0.77
A-2424-FJDH-SS	24	1 1/2	38.1	24	1 7/8-12	43.4	50	55	1.98
A-3232-FJDH-SS	32	2	50.8	32	2 1/2-12	49.0	65	70	3.09

JIC FEMALE 37° SEAT – DOUBLE HEX STAINLESS STEEL

45° JIC FEMALE SWIVEL 37° SEAT

Part Number	Dash Size	Hose ID Size		F Thread		C Cut-Off	D	Hex Dia.	Weight
		(in)	(mm)	Dash Size	Size (in) - TPI	Factor (mm)	Drop (mm)	CH2 (mm)	(lbs/each)
A-0404-FJ45-SS	04	1/4	6.4	04	7/16-20	36.6	10.0	16	0.08
A-0606-FJ45-SS	06	3/8	9.5	06	9/16-18	46.3	11.0	19	0.13
A-0808-FJ45-SS	08	1/2	12.7	08	3/4-16	51.6	15.0	25	0.23
A-1010-FJ45-SS	10	5/8	15.9	10	7/8-14	62.2	19.0	27	0.39
A-1212-FJ45-SS	12	3/4	19.0	12	1 1/16-12	67.5	21.0	32	0.62
A-1616-FJ45-SS	16	1	25.4	16	1 5/16-12	79.5	24.0	38	0.88

90° JIC FEMALE SWIVEL 37° SEAT MEDIUM DROP

Part Number	Dash Size	Hose ID Size		F Thread		C Cut-Off	D	Hex Dia.	Weight
		(in)	(mm)	Dash Size	Size (in) - TPI	Factor (mm)	Drop (mm)	CH2 (mm)	(lbs/each)
A-0404-FJ9M-SS	04	1/4	6.4	04	7/16-20	34.2	32.0	16	0.10
A-0606-FJ9M-SS	06	3/8	9.5	06	9/16-18	31.3	35.0	19	0.15
A-0808-FJ9M-SS	08	1/2	12.7	08	3/4-16	37.2	40.0	25	0.26
A-1010-FJ9M-SS	10	5/8	15.9	10	7/8-14	49.4	48.0	27	0.40
A-1212-FJ9M-SS	12	3/4	19.0	12	1 1/16-12	52.4	54.0	32	0.68
A-1616-FJ9M-SS	16	1	25.4	16	1 5/16-12	72.6	71.5	38	1.01

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.



CAUTIONARY STATEMENT

AII Products sold and distributed by Kuriyama of America, Inc. are commodities and are sold based on their ability to perform within each product's published specifications. The Products are not sold for particular purposes, uses or applications. Purchasers and users are solely responsible for determining whether the Products are suitable for the purchaser's or user's intended purposes, uses or applications. Purchasers and users shall conduct their own engineering studies or tests, or retain qualified engineers, consultants or testing laboratories before determining the proper use, suitability or propriety of the Products. Alfagomma and Piranha Hose hoses and fittings are designed, engineered and tested to be used together in an assembly. Alfagomma and Piranha Hose do not recommend or authorize the use of their hoses or fittings with another manufacturer's hoses or fittings, as doing so may result in unreliable or unsafe assemblies.

Purchasers and users should follow all instructions contained in the catalogs, brochures, technical bulletins and other documents of Kuriyama of America, Alfagomma and Piranha Hose. Kuriyama of America, Alfagomma and Piranha Hose recommend only those hose and coupling combinations specified in the applicable Hydraulic Products Catalogs. The Products, including but not limited to, hose, tubing or couplings, may fail due to the use or conveyance of substances at elevated or lowered temperatures or at excessive pressure, the conveyance of abrasive, injurious, flammable, explosive or damaging substances.

Hose or tubing used in bent configurations will be subjected to increased abrasion. Hose clamps or couplings may loosen after initial installation, and all sections of hose and tubing – including connections, couplings, clamps, conductivity and bonding – should be inspected frequently, regularly and consistently, and should be replaced, adjusted or re-tightened to avoid leakage, prevent injuries or damage, and for general safety purposes.

Purchasers or users of the Products should frequently and consistently undertake inspections and protective measures with respect to the use and application of Products, which should include the examination of tube and cover, conditions of the hose or tubing, and the identification, repair or replacement of sections showing cracking, blistering, separations, internal and external abrasions, leaking or slipped couplings or connections and make proper proof tests.

Kuriyama of America, Alfagomma and Piranha Hose shall not be liable or responsible for hose assemblies that have not been produced in conformance with their assembly recommendations and current crimp data charts.

LIMITED WARRANTY AND LIMITATION OF LIABILITY

The Products sold or distributed by Kuriyama of America are warranted to its customers to be free from defects in material and workmanship at the time of shipment by us, subject to the following provisions. ALL WARRANTY CLAIMS SHALL BE MADE WITHIN SIX (6) MONTHS AFTER KURIYAMA OF AMERICA SHIPPED THE PRODUCTS. KURIYAMA OF AMERICA'S LIABILITY HEREUNDER IS LIMITED, AT KURIYAMA OF AMERICA'S EXCLUSIVE DISCRETION, TO 1) REFUND OF THE PURCHASE PRICE PAID TO IT FOR DEFECTIVE PRODUCTS; OR 2) REPLACEMENT OF ANY DEFECTIVE PRODUCT OR PART UPON ITS AUTHORIZED RETURN TO KURIYAMA OF AMERICA.

THIS LIMITED WARRANTY IS IN LIEU OF AND EXCLUDES ALL OTHER WARRANTIES, EXPRESSED, IMPLIED, STATUTORY, OR OTHERWISE CREATED UNDER APPLICABLE LAW INCLUDING, BUT NOT LIMITED TO, ANY WARRANTY OF MERCHANTABILITY AND ANY WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE. IN NO EVENT SHALL KURIYAMA OF AMERICA, ALFAGOMMA OR PIRANHA HOSE BE LIABLE FOR SPECIAL, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, INCLUDING LOSS OF PROFITS, WHETHER OR NOT CAUSED BY OR RESULTING FROM THE NEGLIGENCE OF KURIYAMA OF AMERICA, ALFAGOMMA OR PIRANHA HOSE.

IN ADDITION, THIS WARRANTY SHALL NOT APPLY TO ANY PRODUCTS OR PORTIONS THEREOF WHICH HAVE BEEN SUBJECTED TO ABUSE, MISUSE, IMPROPER INSTALLATION, MAINTENANCE, OR OPERATION, ELECTRICAL FAILURE OR ABNORMAL CONDITIONS, AND TO PRODUCTS WHICH HAVE BEEN TAMPERED WITH, ALTERED, MODIFIED, REPAIRED, REWORKED BY ANYONE NOT APPROVED BY SELLER, OR USED IN ANY MANNER INCONSISTENT WITH THE PROVISIONS OF THE "CAUTIONARY STATEMENT" ABOVE OR ANY INSTRUCTIONS, MATERIALS OR SPECIFICATIONS PROVIDED WITH OR FOR THE PRODUCT.

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.





Kuriyama of America – Huntley



Kuriyama of America – Reno



Kuriyama of America - Houston



Fortney Sales Co.



Eastern Rubber & Plastics Co.

Distributed by:



Kuriyama De México



CORPORATE OFFICE

150 N Martingale Road, Suite 900, Schaumburg, IL 60173-2081 Phone: (847) 755-0360 • Toll-free Fax: (800) 800-0320 International Fax: (847) 885-0996









The trademarks contained in this publication are trademarks of Kuriyama of America, Inc.

©2024 Kuriyama of America, Inc. All rights reserved.

SALES & WAREHOUSE LOCATIONS

CENTRAL DISTRIBUTION CENTER

 KURIYAMA OF AMERICA, INC.

 14200 Commerce Court

 Huntley, IL 60142

 € (847) 755-0360

 Im (800) 800-0320

 ⊕ kuriyama.com

SOUTHWEST WAREHOUSE

 KURIYAMA OF AMERICA, INC.

 - HOUSTON

 200 Portwall Street, Suite 100

 Houston, TX 77029

 ↓ (713) 674-8212

 ○ (713) 674-5214

 ○ (713) 674-5214

 ○ (713) 674-5214

 ○ (800) 800-5214

 ▷ sales@kuriyama.com

WESTERN WAREHOUSE

KURIYAMA OF AMERICA, INC. - *RENO* 12910 Old Virginia Road, Suite 100 Reno, NV 89521 € (562) 941-4507 1 (562) 941-8940 OR 1 (800) 326-8940 ⊠ sales@kuriyama.com

SOUTHEAST WAREHOUSE

FORTNEY SALES CO., INC. 4221 Cantrell Road NW Acworth, GA 30101 ↓ (770) 427-6528 1 (770) 423-9249 OR 1 (800) 423-9249 ⊕ FortneySales.com sales@fortneysales.com

EASTERN WAREHOUSE

EASTERN RUBBER & PLASTICS CO., INC. 100 Goldman Dr. Plumsted Industrial Park Cream Ridge, NJ 08514 Subset (609) 758-0100 Gold (609) 758-0102 OR Gold (800) 445-7138 Gold EasternRubber.com Sales@easternrubber.com

IN MEXICO

KURIYAMA DE MÉXICO S DE RL DE CV Av Jose Palomo Martinez No 520-20 Bodega 5 Parque Industrial Omolap Apodaca, N.I. CP:66633, México € (81) 1086-1870 0 71 ⊕ Kuriyama.com.mx ⊕ Kuriyama.com ⊠ servicioalcliente@kuriyama.com