

The World's TOUGHEST Fire Hose

COLOR:



General Applications:

- Active municipal departments
- Heavy industrial municipalities
- Refining, chemical and utility industries
- Coarse, abrasive landscapes
- Marine environments
- Daily use applications such as wash down and sewage treatment plants

Construction:

Revolutionary co-extrusion technology creates a “Four Layer Hose-In-One Operation” without the use of glues or adhesives thereby forming a homogeneous hose which cannot delaminate.

Service Temperature Range:

-4°F (-20°C) to +176°F (+80°C)

Features and Advantages:

- Resists burn-through.
- Super resistant to abrasion.
- Underwriters Laboratories (UL) 19 and Underwriters Laboratories of Canada (ULC) – S511-14 Certified* – 1 1/2", 1 3/4", 2", 2 1/2".
- Excellent resistance to heat, ozone, weather, most chemicals (acids, bases, salts, oils, solvents, etc.), flame, wear, tear and puncture.
- Highly flexible and smooth inner lining provides excellent dilation characteristics with low friction loss and high kinking resistance.
- Meets or exceeds National Fire Protection Association (NFPA) 1961 Standard on Fire Hose (current edition).
- ISO 9001 - JAFx4 fire hose products are manufactured in a registered facility in Barcelona, Spain.
- 10-year warranty.

Packaging:

Available in 25', 50' and 100' lengths.



BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS OR DISCONTINUE PRODUCTS WITHOUT PRIOR NOTICE.

Bulk Hose Lengths

| Nominal Specifications | | | | | | | | |
|------------------------|-----------|--------|----------------|--------------------|------------------|------------------|------------------------|---------------------------|
| Part Number* | Size (in) | Color | Bowl Size (in) | Service Test (psi) | Proof Test (psi) | Burst Test (psi) | Available Lengths (ft) | Weight Uncoupled (lbs/ft) |
| 56H1FX4-XX | 1 | Yellow | 1 3/16 | 580 | 1160 | 1740 | 25/50/100 | 0.160 |
| 56H15FX4-XX | 1 1/2 | Yellow | 1 3/4 | 300 | 600 | 900 | 25/50/100 | 0.296 |
| 56H175FX4-XX | 1 3/4 | Yellow | 2 1/16 | 300 | 600 | 900 | 25/50/100 | 0.343 |
| 56H2FX4-XX | 2 | Yellow | 2 9/32 | 300 | 600 | 900 | 25/50/100 | 0.390 |
| 56H25FX4-XX | 2 1/2 | Yellow | 2 13/16 | 300 | 600 | 900 | 25/50/100 | 0.517 |
| 56H4FX4-XX | 4 | Yellow | 4 9/32 | 250 | 500 | 750 | 25/50/100 | 0.874 |
| 56H5FX4-XX | 5 | Yellow | 5 3/8 | 250 | 500 | 750 | 25/50/100 | 1.109 |

*XXX = Available Lengths

Assembled Lengths

| Nominal Specifications | | | | | | | | | | |
|------------------------|-----------|--------|--------------------|---------------|----------------|--------------------|------------------|------------------|------------------------|---------------------------|
| Part Number* | Size (in) | Color | Coupling Size (in) | Coupling Type | Bowl Size (in) | Service Test (psi) | Proof Test (psi) | Burst Test (psi) | Available Lengths (ft) | Weight Uncoupled (lbs/ft) |
| JX100YXXX-NH100 | 1 | Yellow | 1 | NST | 1 3/16 | 580 | 1160 | 1740 | 25/50/100 | 0.160 |
| JX100YXXX-NP100 | 1 | Yellow | 1 | NPSH | 1 3/4 | 580 | 1160 | 1740 | 25/50/100 | 0.160 |
| JX150YXXX-NH150 | 1 1/2 | Yellow | 1 1/2 | NST | 1 3/4 | 300 | 600 | 900 | 25/50/100 | 0.296 |
| JX150YXXX-NP150 | 1 1/2 | Yellow | 1 1/2 | NPSH | 1 3/4 | 300 | 600 | 900 | 25/50/100 | 0.296 |
| JX175YXXX-NH150 | 1 3/4 | Yellow | 1 1/2 | NST | 2 1/16 | 300 | 600 | 900 | 25/50/100 | 0.343 |
| JX175YXXX-NP150 | 1 3/4 | Yellow | 1 1/2 | NPSH | 2 1/16 | 300 | 600 | 900 | 25/50/100 | 0.343 |
| JX200YXXX-NH150 | 2 | Yellow | 1 1/2 | NST | 2 9/32 | 300 | 600 | 900 | 25/50/100 | 0.390 |
| JX200YXXX-NP150 | 2 | Yellow | 1 1/2 | NPSH | 2 9/32 | 300 | 600 | 900 | 25/50/100 | 0.390 |
| JX250YXXX-NH250 | 2 1/2 | Yellow | 2 1/2 | NST | 2 13/16 | 300 | 600 | 900 | 25/50/100 | 0.517 |
| JX400YXXX-SZ400 | 4 | Yellow | 4 | Storz | 4 9/32 | 250 | 500 | 750 | 25/50/100 | 0.874 |
| JX500YXXX-SZ500 | 5 | Yellow | 5 | Storz | 5 3/8 | 225 | 450 | 675 | 25/50/100 | 1.109 |

*XXX = Available Lengths

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS OR DISCONTINUE PRODUCTS WITHOUT PRIOR NOTICE.