

-	BCAP2	231
	BHN	236
	ВНҮА	231
	BRGHT2	234
	BRGHT-FEM2	234
	BRGHT-M 2	234
	BRNPS2	235
	BRNPS-FEM2	235
	BRNPS-M 2	235
8	DMHN	233

Index

	FMHN 2	232
\bigcirc	HYD 2	237
0	GHG 2	237
es la	SW	230
G=	= SWDA2	229
á	= SWHA2	229
	- SWLA	229
\$	SWU 2	230
	Viper® VTE 2	228

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.



kuriyama.com



VTE-1550



VTE-2510







Industrial Hose Nozzles

GENERAL APPLICATIONS

- General plant wash-down service.
- Dust control.
- Wildland firefighting.

CONSTRUCTION

- Composite housing with brass stem and rubber bumper.
- Female NST or NPSH threads.
- Fixed teeth.
- Available in Red or Black colors.

FEATURES AND ADVANTAGES

- Adjustable flow control with twisting nozzle adjusts spray pattern from full stream to misting fog.
- Impact resistant, rubber bumpers protect nozzle from damage if dropped or dragged.
- Lightweight and compact design reduces worker fatigue.

APPROVALS AND STANDARDS

The VIPER[®] VTE[™] is National Fire Protection Association (NFPA) 1964 compliant and is manufactured in an ISO 9001 accredited facility. European Standards (EN) 15182-1 and EN15182-2 type 3 Certificates are available by request.

Part Number	Model Rigid Inlet		Color	Nozzle Flow		Len	Length		Weight (Each)	
Fait Number	Number (In)	(In)	(In)		(lpm)	(in)	(cm)	(lbs)	(kg)	
I150006C	VTE-1550	1 NST	Red	30	125	5.30	13	0.44	0.20	
I150004C	VTE-1550	1 NPSH	Red	30	125	5.30	13	0.44	0.20	
I150005C	VTE-1550	1 NST	Black	30	125	5.30	13	0.44	0.20	
1150034	VTE-2510	1 1/2 NST	Red	95	360	5.90	15	0.66	0.30	
1218950	VTE-2510	1 1/2 NPSH	Red	95	360	5.90	15	0.66	0.30	
1150015	VTE-2510	1 1/2 NST	Black	95	360	5.90	15	0.66	0.30	

NOTE: Please refer to the Kuriyama Fire Products[™] Fire Nozzle Catalog or KuriyamaFire.com, for our complete line of fire nozzles for municipal and firefighting use.













VIEW ONLINE -

SCAN FOR INFO or visit

KOA.link/Hydrant-

Wrenches



Heavy Duty Adjustable Hydrant Wrench

SWDA Series

Heavy Duty Adjustable Hydrant Wrench

SWLA Series

Adjustable Hydrant Wrench

FEATURES AND ADVANTAGES

- Designed to open and close hydrant caps and valves.
- Also can be used with rocker lug and pin lug style hose couplings.

MATERIAL SPECIFICATIONS


- Ductile iron plated body ASTM A536, Grade 65-45-12.
- Plated carbon steel handle ASTM A29, Grade 1030.

Part Number	Size Range (in)	Handle Diameter (in)	Handle Length (in)	Weight Each (lbs)	Standard Cartor
SWHA	1 1/2 - 6	0.875	15.75	4.79	12
Part Number	Size Range (in)	Handle Diameter (in)	Handle Length (in)	Weight Each (Ibs)	Standard Cartor
SWDA	1 1/2 - 6	0.875	15.75	4.41	12

Part Number	Size Range (in)	Handle Diameter (in)	Handle Length (in)	Weight Each (Ibs)	Standard Carton
SWLA	1 1/2 - 3	0.750	14.25	2.93	12







- VIEW ONLINE -

SCAN FOR INFO or visit KOA.link/Spanner-Wrenches

SW Series

Spanner Wrench

SWU Series

Universal Spanner Wrench

FEATURES AND ADVANTAGES

- Designed for use with male and female pin lug couplings .
- Used to tighten collar on pin lugs to provide a tight seal.

MATERIAL SPECIFICATIONS

• Ductile iron plated ASTM A536, Grade 65-45-12.

Part Number	Size (in)	Weight Each (Ibs)	Standard Carton
SW150	1 1/2	0.44	100
SW200	2	0.60	100
SW300	3	0.99	50
SW400	4	1.30	40

Part Number	Size (in)	Weight Each (Ibs)	Standard Carton
SWU	1 1/2 - 4 1/2	1.59	30









VIEW ONLINE -

G SCAN FOR INFO

or visit

KOA.link/BHYA-BCAP



Female to Male Brass Hydrant Adapter

BCAP Series

Brass Hydrant Cap

FEATURES AND ADVANTAGES

- Designed for use in connection of hoses, nozzles, hydrants, pipes, or other fittings using NST, NPSH, or GHT threads.
- Made of heavy-duty brass material.
- Brass adapters are more durable and heat resistant than aluminum adapters.

MATERIAL SPECIFICATIONS

• Brass ASTM B584, Grade C85700.

Part Number	Female Thread (in)	Male Thread (in)	PSI Rating at 70°F	Weight Each (lbs)	Standard Cartor
BHYA-24ST12GH	1 1/2 NST	3/4 GHT	300	0.52	100
BHYA-40ST12GH	2 1/2 NST	3/4 GHT	300	1.16	50
BHYA-40ST16SH	2 1/2 NST	1 NPSH	300	1.03	50
BHYA-40ST24SH	2 1/2 NST	1 1/2 NPSH	300	1.00	40
BHYA-40ST32SH	2 1/2 NST	2 NPSH	300	1.07	40
BHYA-24ST24PT	1 1/2 NST	1 1/2 NPT	300	0.60	100
BHYA-40ST12PT	2 1/2 NST	3/4 NPT	300	0.90	50
BHYA-40ST16PT	2 1/2 NST	1 NPT	300	1.02	50
BHYA-40ST24PT	2 1/2 NST	1 1/2 NPT	300	0.91	40
BHYA-40ST32PT	2 1/2 NST	2 NPT	300	1.11	40
BHYA-48PT405T	3 NPT	2 1/2 NST	300	1.48	20
BHYA-40ST24ST	2 1/2 NST	1 1/2 NST	300	0.98	40
BHYA-48ST40ST	3 NST	2 1/2 NST	300	1.72	20
BHYA-24SH24ST	1 1/2 NPSH	1 1/2 NST	300	0.60	100
BHYA-48SH40ST	3 NPSH	2 1/2 NST	300	1.42	20
BHYA-24SH24PT	1 1/2 NPSH	1 1/2 NPT	300	0.60	100

Part Number	Size (in)	PSI Rating at 70°F	Weight Each (lbs)	Standard Carton
BCAP-24SH	1 1/2 NPSH	300	0.55	100
BCAP-24ST	1 1/2 NST	300	0.53	100
BCAP-40SH	2 1/2 NPSH	300	1.41	50
BCAP-40ST	2 1/2 NST	300	1.32	50







VIEW ONLINE -



or visit KOA.link/FMHN

FMHN Series

Female to Male Brass Hex Nipple

FEATURES AND ADVANTAGES

- Designed for use in connection of hoses, nozzles, hydrants, pipes, or other fittings using NST, NPSH, or GHT threads.
- Made of heavy-duty brass material.
- Brass adapters are more durable and heat resistant than aluminum adapters.

MATERIAL SPECIFICATIONS

• Brass ASTM B584, Grade C85700.

Part Number	Female Thread (in)	Male Thread (in)	PSI Rating at 70°F	Weight Each (Ibs)	Standard Carton
FMHN-12GH16PT	3/4 GHT	1 NPT	300	0.25	200
FMHN-16PT12GH	1 NPT	3/4 GHT	300	0.26	100
FMHN-24PT24SH	1 1/2 NPT	1 1/2 NPSH	300	0.51	100
FMHN-40PT40SH	2 1/2 NPT	2 1/2 NPSH	300	1.33	20
FMHN-24PT24ST	1 1/2 NPT	1 1/2 NST	300	0.53	100
FMHN-40PT40ST	2 1/2 NPT	2 1/2 NST	300	1.20	25
FMHN-48PT40ST	3 NPT	2 1/2 NST	300	2.92	20
FMHN-16SH12GH	1 NPSH	3/4 GHT	300	0.25	100
FMHN-24SH24PT	1 1/2 NPSH	1 1/2 NPT	300	0.49	100
FMHN-24SH24ST	1 1/2 NPSH	1 1/2 NST	300	0.55	100
FMHN-40SH40ST	2 1/2 NPSH	2 1/2 NST	300	1.20	25
FMHN-24ST24PT	1 1/2 NST	1 1/2 NPT	300	0.44	100
FMHN-24ST24SH	1 1/2 NST	1 1/2 NPSH	300	0.49	100
FMHN-40ST32PT	2 1/2 NST	2 NPT	300	2.29	30
FMHN-40ST40PT	2 1/2 NST	2 1/2 NPT	300	1.76	20
FMHN-40ST48PT	2 1/2 NST	3 NPT	300	2.43	20
FMHN-40ST40SH	2 1/2 NST	2 1/2 NPSH	300	1.59	20
FMHN-40ST48ST	2 1/2 NST	3 NST	300	2.43	20
FMHN-48ST40ST	3 NST	2 1/2 NST	300	2.87	20











DMHN Series

Male to Male Brass Hex Nipple

FEATURES AND ADVANTAGES

- Designed for use in connection of hoses, nozzles, hydrants, pipes, or other fittings using NST, NPSH, or GHT threads.
- Made of heavy-duty brass material.
- Brass adapters are more durable and heat resistant than aluminum adapters.

MATERIAL SPECIFICATIONS

• Brass ASTM B584, Grade C85700.

Part Number	Male Thread (in)	Male Thread (in)	PSI Rating at 70°F	Weight Each (Ibs)	Standard Carton
DMHN-16PT12GH	1 NPT	3/4 GHT	300	0.26	200
DMHN-16PT16SH	1 NPT	1 NPSH	300	0.33	100
DMHN-24PT24SH	1 1/2 NPT	1 1/2 NPSH	300	0.52	100
DMHN-32PT32SH	2 NPT	2 NPSH	300	1.25	50
DMHN-40PT40SH	2 1/2 NPT	2 1/2 NPSH	300	1.03	25
DMHN-16PT16ST	1 NPT	1 NST	300	0.51	100
DMHN-24PT24ST	1 1/2 NPT	1 1/2 NST	300	0.48	100
DMHN-32PT40ST	2 NPT	2 1/2 NST	300	1.34	30
DMHN-40PT40ST	2 1/2 NPT	2 1/2 NST	300	1.26	25
DMHN-48PT40ST	3 NPT	2 1/2 NST	300	2.14	20
DMHN-24ST24ST	1 1/2 NST	1 1/2 NST	300	0.52	100
DMHN-48ST40ST	3 NST	2 1/2 NST	300	2.51	20
DMHN-24ST24SH	1 1/2 NST	1 1/2 NPSH	300	0.49	100









BRGHT Series

Brass Garden Hose Fitting Set

BRGHT-FEM Series

Brass Female Garden Hose Fitting

BRGHT-M Series

Brass Male Garden Hose Fitting

FEATURES AND ADVANTAGES

- Designed for use in connection of hoses, nozzles, hydrants, pipes, or other fittings using NST, NPSH, or GHT threads.
- Made of heavy-duty brass material.
- Brass adapters are more durable and heat resistant than aluminum adapters.

MATERIAL SPECIFICATIONS


• Brass ASTM B124, Grade 37700.

Part Number	Thread Size (in)	Thread	Shank Size (in)	PSI Rating at 70°F	Weight Each (lbs)	Standard Carton
BRGHT050	1/2	GHT	1/2	150	0.25	180
BRGHT062	5/8	GHT	5/8	150	0.25	180
BRGHT075	3/4	GHT	3/4	150	0.25	180
Part Number	Female Thread Size (in)	Female Thread	Shank Size (in)	PSI Rating at 70°F	Weight Each (Ibs)	Standard Carton
BRGHT-FEM050	1/2	GHT	1/2	150	0.12	360
BRGHT-FEM062	5/8	GHT	5/8	150	0.12	360
BRGHT-FEM075	3/4	GHT	3/4	150	0.12	360
Part Number	Male Thread Size (in)	Male Thread	Shank Size (in)	PSI Rating at 70°F	Weight Each (Ibs)	Standard Carton
BRGHT-M050	1/2	GHT	1/2	150	0.13	360
BRGHT-M062	5/8	GHT	5/8	150	0.13	360
BRGHT-M075	3/4	GHT	3/4	150	0.13	360











BRNPS Series

Brass Garden Hose Fitting Set

BRNPS-FEM Series

Brass Female Garden Hose Fitting

BRNPS-M Series

Brass Male Garden Hose Fitting

FEATURES AND ADVANTAGES

- Designed for use in connection of hoses, nozzles, hydrants, pipes, or other fittings using NST, NPSH, or GHT threads.
- Made of heavy-duty brass material.
- Brass adapters are more durable and heat resistant than aluminum adapters.

MATERIAL SPECIFICATIONS

• Brass ASTM B124, Grade 37700.

Part Number	Thread Size (in)	Thread	Shank Size (in)	PSI Rating at 70°F	Weight Each (lbs)	Standard Carton
BRNPS100	1	NPS	1	150	0.49	120
Part Number	Female Thread Size (in)	Female Thread	Shank Size (in)	PSI Rating at 70°F	Weight Each (Ibs)	Standard Carton
BRNPS-FEM100	1	NPS	1	150	0.25	240
Part Number	Male Thread Size (in)	Male Thread	Shank Size (in)	PSI Rating at 70°F	Weight Each (Ibs)	Standard Carton
BRGHT-M100	1	NPS	1	150	0.25	240







or visit KOA.link/BHN

BHN Series

Brass Hose Nozzle

FEATURES AND ADVANTAGES

- Designed for use in connection of hoses, nozzles, hydrants, pipes, or other fittings using NST, NPSH, or GHT threads.
- Made of heavy-duty brass material.
- Brass adapters are more durable and heat resistant than aluminum adapters.

MATERIAL SPECIFICATIONS


• Brass ASTM B124, Grade 37700.

Part Number	Female Thread Size (in)	Nozzle Hole Size (in)	Thread (in)	PSI Rating at 70°F	Weight Each (lbs)	Standard Carton
BHN-1206GH	3/4 GHT x 6	5/16	GHT	6	0.37	100
BHN-1206SH	3/4 NPSH x 6	5/16	NPSH	6	0.37	100
BHN-1608SH	1 NPSH x 8	5/16	NPSH	8	0.68	50
BHN-2010SH	1 1/4 NPSH x 10	7/16	NPSH	10	1.23	30
BHN-2410SH	1 1/2 NPSH x 10	1/2	NPSH	10	1.32	30
BHN-2410ST	1 1/2 NST x 10	1/2	NST	10	1.32	30
BHN-3212SH	2 NPSH x 12	13/16	NPSH	12	2.09	20
BHN-4012SH	2 1/2 NPSH x 12	13/16	NPSH	12	2.87	20
BHN-4012ST	2 1/2 NST x 12	13/16	NST	12	2.87	15









GHG Series

EPDM Garden Hose Gasket

HYD Series

EPDM Hydrant Hose Gasket

	SCAN FOR INFO			
	or visit			
	KOA.link/GHG-HYD			

Part Number	Size (in)	Thread	Weight Each (Ibs)	Standard Carton
GHG075	3/4	GHT	0.003	100
GHG100	1	GHT	0.004	100
Part Number	Size (in)	Thread	Weight Each (Ibs)	Standard Carton
HYD-ST150	1 1/2	NST	0.008	100
HYD-SH150	1 1/2	NPSH	0.008	100
HYD200	2	NST/NPSH	0.012	100
HYD-ST250	2 1/2	NST	0.017	100
HYD-SH250	2 1/2	NPSH	0.031	100
HYD300	3	NST/NPSH	0.031	100

