

 **KURIYAMA INDUSTRIAL HOSE**

 **King Bee**

by Kuriyama

Liquid Suction and Wastewater Hose

*Highly Flexible – great
for portable toilets*

Crush Resistant

Wear Resistant



KBEE™ Series



 **MADE IN THE
USA**

 **KURIYAMA**
OF AMERICA, INC.

kuriyama.com

EDITION 0124



KBEE™ Series

Polyethylene Liquid Suction and Wastewater Hose

GENERAL APPLICATIONS

- Pumps, rental and construction dewatering
- Pumps, trash
- Septic and wastewater handling
- Water suction – standard duty

CONSTRUCTION

Flexible polyethylene (LDPE) tube with polyethylene (LDPE) ribs and cuffed ends.

SERVICE TEMPERATURE RANGE

-40°F (-40°C) to +150°F (+65°C)*

**Actual service temperature range is application dependent.*

VIEW ONLINE



SCAN FOR INFO
or visit
KOA.link/KBEE

FEATURES AND ADVANTAGES

- **Superior Flexibility!** – Corrugated tube and ribs provides high flexibility, perfect for maneuvering in tight areas such as portable toilets.
- **“Cold-Flex” Materials** – Hose remains flexible in sub-zero temperatures.
- **Crush Resistant** – Will spring back to original shape after being crushed, will not kink!
- **Easy Slide Helix** – Exposed ribs protect hose tube from cover wear, and allow hose to slide easily over rough surfaces. Easy-to-handle.
- **Leak Proof Cuffs** – Overmolded cuffs eliminate leaking and will not separate from the hose. Each cuff and unit is 100% factory tested.
- **Additional Cuffs** – Additional 2" and 3" cuffs are available for making hose repairs and custom lengths.

Series Number	ID		OD		Working Pressure at 68°F (psi)	Vacuum Rating Hg at 68°F (in)	Min. Bending Radius at 68°F (in)	Standard Length (ft)	Weight (lbs/ft)
	(in)	(mm)	(in)	(mm)					
KBEE200	2	52.7	2.76	69.5	15	29	3.5	60/50/40/30/25/20/10	0.72
KBEE300	3	76.0	4.06	97.0	7	29	6.5	60/50/30/25/20	1.36

NOTE: Service life may vary depending on operating conditions and type of material being conveyed.



CUFF Series


King Bee Additional Cuffs

Part Number	ID (in)	Weight (lbs)
CUFF2	2	0.20
CUFF3	3	0.27

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.

KBEE™ Series

Polyethylene Hose Guard



VIEW ONLINE



SCAN FOR INFO
or visit
KOA.link/KBEE

GENERAL APPLICATIONS

- Protection of high pressure sewer jetting hoses

CONSTRUCTION

Flexible polyethylene (LDPE) tube with polyethylene (LDPE) ribs and cuffed ends.

SERVICE TEMPERATURE RANGE

-40°F (-40°C) to +150°F (+65°C)*

**Actual service temperature range is application dependent.*

FEATURES AND ADVANTAGES

- **Easy Slide Interior** – Low coefficient of friction polyethylene tube allows for sewer jetting hoses to slide through easily, protecting them from wear.
- **“Cold-Flex” Materials** – Remains flexible in sub-zero temperatures.
- **Crush Resistant** – Will spring back to original shape after being crushed, will not kink!
- **Easy Slide Helix** – Exposed ribs protect tube from cover wear, and allow hose to slide easily over rough surfaces. Easy-to-handle.
- **Leak Proof Cuffs** – Overmolded cuffs will not separate from the hose guard. Each cuff and unit is 100% factory tested.

Part Number	ID		OD		Working Pressure at 68°F (psi)	Vacuum Rating Hg at 68°F (in)	Min. Bending Radius at 68°F (in)	Standard Length (ft)	Weight (lbs/ft)
	(in)	(mm)	(in)	(mm)					
KBEE2X3	2	50.8	2.76	70.1	15	29	3.5	3	2.55
KBEE3X3	3	76.2	4.06	103.1	7	29	6.5	3	4.80

NOTE: Service life may vary depending on operating conditions and type of material being conveyed.



KBC™ Series

King Bee™ Collar Clamp with 20' Rope

- Available in carbon steel or corrosion resistant stainless steel



(Hose sold separately)

Part Number	ID (in)	Material	Weight (lbs)
KBC-CS300	3	Carbon Steel	0.64
KBC300	3	Stainless Steel	0.67

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.

Cautionary Statement

All Products sold and distributed by Kuriyama of America, Inc. are in the nature of commodities and they are sold by published specifications and not for particular purposes, uses or applications. Purchaser shall first determine their suitability for the intended purposes, uses or applications and shall either conduct its own engineering studies or tests, or retain qualified engineers, consultants or testing laboratories and consult with them before determining the proper use, suitability or propriety of the merchandise or Products for the intended purposes, uses or applications.

Kuriyama of America, Inc. ("Seller") does not recommend the Products for any particular purpose, use or application, and the Purchaser or user thereof shall assume full responsibility for the suitability, propriety, use and application of the Products. Purchaser shall follow all instructions contained in Seller's catalogs, brochures, technical bulletins and other documents regarding the Products. The Products, including but not limited to, hose, tubing or couplings, may fail due to the use or conveyance of substances at elevated or lowered temperatures or at excessive pressure, the conveyance of abrasive, injurious, flammable, explosive or damaging substances.

Hose or tubing used in bent configurations will be subjected to increased abrasion. Hose clamps or couplings may loosen after initial installation and all sections of hose and tubing including connections, couplings, clamps, conductivity and bonding should be inspected frequently, regularly and consistently, and should be replaced, adjusted or re-tightened for the avoidance of leakage, for the prevention of injuries or damages, and for general safety purposes. Except as indicated in its Limited Warranty, Seller shall not be liable or responsible for direct or indirect injuries or damages caused by or attributed to the failure or malfunction of any Products sold or distributed by it.

Purchasers or users of the Products should frequently and consistently undertake inspections and protective measures with respect to the use and application of Products, which should include the examination of tube and cover, conditions of the hose or tubing, and the identification, repair or replacement of sections showing cracking, blistering, separations, internal and external abrasions, leaking or slipped couplings or connections and make proper proof tests.

Limited Warranty

The Products sold or distributed by Seller are warranted to its customers to be free from defects in material and workmanship at the time of shipment by us, subject to the following provisions. ALL WARRANTY CLAIMS SHALL BE MADE WITHIN SIX (6) MONTHS AFTER SELLER SHIPPED THE PRODUCTS. SELLER'S LIABILITY HEREUNDER IS LIMITED AT SELLER'S EXCLUSIVE DISCRETION, TO 1) THE PURCHASE PRICE OF ANY PRODUCTS PROVING DEFECTIVE; 2) REPAIR OF ANY DEFECTIVE PRODUCT OR PART THEREOF; OR 3) REPLACEMENT OF ANY DEFECTIVE PRODUCT OR PART UPON ITS AUTHORIZED RETURN TO SELLER.

THIS WARRANTY IS IN LIEU OF AND EXCLUDES ALL OTHER WARRANTIES, EXPRESSED, IMPLIED, STATUTORY, OR OTHERWISE CREATED UNDER APPLICABLE LAW INCLUDING, BUT NOT LIMITED TO, THE WARRANTY OF MERCHANTABILITY AND THE WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE. IN NO EVENT SHALL SELLER OR THE MANUFACTURER OF THE PRODUCT BE LIABLE FOR SPECIAL, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, INCLUDING LOSS OF PROFITS, WHETHER OR NOT CAUSED BY OR RESULTING FROM THE NEGLIGENCE OF SELLER AND/OR THE MANUFACTURER OF THE PRODUCT, UNLESS SPECIFICALLY PROVIDED HEREIN. IN ADDITION, THIS WARRANTY SHALL NOT APPLY TO ANY PRODUCTS OR PORTIONS THEREOF WHICH HAVE BEEN SUBJECTED TO ABUSE, MISUSE, IMPROPER INSTALLATION, MAINTENANCE, OR OPERATION, ELECTRICAL FAILURE OR ABNORMAL CONDITIONS, AND TO PRODUCTS WHICH HAVE BEEN TAMPERED WITH, ALTERED, MODIFIED, REPAIRED, REWORKED BY ANYONE NOT APPROVED BY SELLER, OR USED IN ANY MANNER INCONSISTENT WITH THE PROVISIONS OF THE "CAUTIONARY STATEMENT" ABOVE OR ANY INSTRUCTIONS OR SPECIFICATIONS PROVIDED WITH OR FOR THE PRODUCT.

05/03/21 REV

Distributed by:



KURIYAMA
OF AMERICA, INC.

HEADQUARTERS AND SALES OFFICE

150 N Martingale Road, Schaumburg, IL 60173-5335
Phone: (847) 755-0360 • Toll-free Fax: (800) 800-0320

International Fax: (847) 885-0996



kuriyama.com



sales@kuriyama.com



The trademarks contained in this publication are trademarks of Kuriyama of America, Inc.

SALES & WAREHOUSE LOCATIONS

CENTRAL DISTRIBUTION CENTER

KURIYAMA OF AMERICA, INC.
– HUNTLEY
14200 Commerce Court
Huntley, IL 60142

SOUTHWEST WAREHOUSE

KURIYAMA OF AMERICA, INC.
– HOUSTON
200 Portwall Street, Suite 100
HOUSTON, TX 77029
Phone: (713) 674-8212
Toll Free Phone: (800) 501-6808
FAX: (713) 674-5214
Toll Free FAX: (800) 800-5214
✉ sales@kuriyama.com

WESTERN WAREHOUSE

KURIYAMA OF AMERICA, INC.
– RENO
12910 Old Virginia Road, Suite 100
Reno, NV 89521
Phone: (562) 941-4507
FAX: (562) 941-8940
Toll-Free FAX: (800) 326-8940
✉ sales@kuriyama.com

SOUTHEAST WAREHOUSE

FORTNEY SALES CO., INC.
4221 Cantrell Road NW
Acworth, GA 30101
Phone: (770) 427-6528
FAX: (770) 423-9249
Toll Free FAX: (800) 423-9249
🌐 FortneySales.com ✉ sales@fortneysales.com

EASTERN WAREHOUSE

EASTERN RUBBER & PLASTICS CO., INC.
100 Goldman Dr.
Plumsted Industrial Park
Cream Ridge, NJ 08514
Phone: (609) 758-0100
FAX: (609) 758-0102
Toll Free FAX: (800) 445-7138
🌐 EasternRubber.com ✉ sales@easternrubber.com

IN MEXICO

KURIYAMA DE MÉXICO S DE RL DE CV
Av Jose Palomo Martinez No 520-20 Bodega 5
Parque Industrial Omolap
Apodaca, N.I. CP:66633, México
Telefonos: (81) 1086-1870 0 71
🌐 Kuriyama.com.mx 🌐 Kuriyama.com
✉ servicioalcliente@kuriyama.com