



Red Fuel Oil Discharge Hose

General Applications:

- A high quality hose to handle oil, diesel, fuel oil and other petroleum products for home delivery. Also suitable for handling regular and unleaded gasolines up to 93 octane and bio-diesels up to B20.

Construction:

- **Tube** – Black Class A Nitrile, high oil resistance.
- **Reinforcement** – Spiral polyester yarn with static wire.
- **Cover** – Red Class A Nitrile/PVC, high oil resistance.

Service Temperature Range:

Fuel Oils -40°F (-40°C) to +150°F (+70°C) *Gasoline/
 Gasoline Blends -40°F (-40°C) to +104°F (+40°C)
 *Use in Gasoline or Ethanol Blend Applications above
 +104°F (+40°C) is not recommended.

Branding:

REDI-TRANSFER FUEL OIL DELIVERY SIZE-WP-MADE
 IN USA

Packaging:

Cut lengths and bulk reels (maximum 3 pcs. on reel).

Features and Advantages:

- Long lengths on reels.
- High oil resistance (Class A) rated tube and cover.

Redi-Transfer™ Cut Lengths

Nominal Specifications

| Part Number | Color | ID (in) | OD (in) | Working Pressure (psi) | Length (ft) | Weight (lbs/pc) |
|-----------------|-------|---------|---------|------------------------|-------------|-----------------|
| REDITFR-100x100 | RED | 1 | 1.50 | 250 | 100 | 47 |
| REDITFR-100x150 | RED | 1 | 1.50 | 250 | 150 | 71 |
| REDITFR-100x200 | RED | 1 | 1.50 | 250 | 200 | 94 |
| REDITFR-125x100 | RED | 1 1/4 | 1.78 | 250 | 100 | 59 |
| REDITFR-125x125 | RED | 1 1/4 | 1.78 | 250 | 125 | 74 |
| REDITFR-125x150 | RED | 1 1/4 | 1.78 | 250 | 150 | 89 |
| REDITFR-137x125 | RED | 1 3/8 | 1.88 | 250 | 125 | 81 |
| REDITFR-137x150 | RED | 1 3/8 | 1.88 | 250 | 150 | 98 |
| REDITFR-150x125 | RED | 1 1/2 | 2.09 | 250 | 125 | 100 |
| REDITFR-150x150 | RED | 1 1/2 | 2.09 | 250 | 150 | 120 |
| REDITFR-150x175 | RED | 1 1/2 | 2.09 | 250 | 175 | 140 |

Redi-Transfer™ Bulk Hose on Reels

Nominal Specifications

| Part Number | Color | ID (in) | OD (in) | Working Pressure (psi) | Reel Length (ft) | Weight (lbs/pc) |
|-----------------|-------|---------|---------|------------------------|------------------|-----------------|
| REDITFR-100x500 | Red | 1 | 1.50 | 250 | 500 | 235 |
| REDITFR-125x450 | Red | 1 1/4 | 1.78 | 250 | 450 | 265 |
| REDITFR-150x400 | Red | 1 1/2 | 2.09 | 250 | 400 | 320 |

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.